

HPD III (High Pressure Diffuser)

Aerosol Monitoring Accessory

Reduces the pressure of gases for particle counters operating at atmospheric pressure



Without measurement there is no control

The HPD III reduces the pressure of high purity, high pressure gas to near atmospheric pressures to allow for accurate sampling of aerosol particle size channels of $\geq 0.2 \mu\text{m}$ by PMS particle counters. The HPD works by diffusing some of the gas out of the system, allowing the particle counter's flow-metering system to function as designed. The PMS particle counters that the HPD III is compatible with includes AirNet, IsoAir, Lasair Pro, and Lasair III.

The HPD III will effectively reduce the pressure of a gas line from 120 psi to atmospheric pressure and is compatible with non-toxic, non-flammable gases such as Clean Dry Air (CDA), nitrogen (N_2), argon (Ar), and carbon dioxide (CO_2). See the table below for a visualization of what particle counters are compatible with which gases.

HPDIII is available in two configurations:

- HPD III-Low for gas lines pressures less than ~25 psi
- HPD III-High for gas lines pressures between ~20 and 150 psi

See the full table on the next page of gas pressure capabilities.

Particle Counter	CDA	N_2	Ar	CO_2	$\text{O}_2/\text{He}/\text{Ne}/\text{H}_2$
Airnet	Y	Y	N	N	N
Lasair III 110	Y	Y	N	N	N
Lasair III 310	Y	Y	Y	N	N
IsoAir 310P	Y	Y	Y	N	N
IsoAir Pro-E/Plus	Y	Y	Y	Y	N
Lasair Pro	Y	Y	Y	Y	N
HPGP 101-C	Y	Y	Y	Y	Y

BENEFITS

- Measures gases from 5 to 120 psi (range dependent on model and sample gas)
- Can be used with Clean Dry Air (CDA), argon (Ar), nitrogen (N_2), carbon dioxide (CO_2), or other non-toxic inert gases (see table for compatible gases)
- Seven different versions for 0.1 CFM, 1.0 CFM, 50 LPM, and 100 LPM flow rates
- No external flow meters needed
- Economical monitoring of pressurized gases with atmospheric pressure particle counters

FEATURES

- No moving parts to wear
- Connects via male 4-VCR fitting
- Exhaust filter prevents possible room contamination
- Mounting clamps supplied
- Stainless steel construction

APPLICATIONS

- Nano-ID® NPC10 nanoparticle counter
- Lasair® III particle counter models 310, 350, and 5100
- Lasair® III particle counter models 310B, 310C, 350C, and 5100
- Airnet® II particle sensor models 201, 301, 310, 501, 510, and 510XR
- IsoAir® particle counter models 310P, Pro-E, and Pro-Plus

HPD III (High Pressure Diffuser)

Aerosol Monitoring Accessory

Specifications

Pressure	See additional table below
Applicable Sample Flow Rate	0.1 CFM, 1.0 CFM, 50 LPM, or 100 LPM
Particle size range	0.3 – 25 µm
Environment	Temperature: 39 – 86 °F (4 – 30 °C). Humidity: Non-condensing.
Material	Enclosure: 316L stainless steel body, exhaust filter Gaskets: 316 stainless steel, Buna-N O-rings
Inlet fitting	Male 4-VCR fitting, #4 size, class 316L stainless steel with Ruby orifice
Exhaust fitting	Barb fitting for 0.75" ID, 0.5" ID, 0.375" ID, or 0.125" ID dependent upon configuration
ISO class	Less than 5% of ISO Class 5
Tubing length	1 m (39.4 in) maximum
Dimensions (h, w, d)	15 x 2.75 x 5.5 in (38 x 7 x 14 cm)
Weight	2.7 lb (1.25 kg)
Compatible instruments	See the Applications section on the previous page

	Flow Rate	CDA	Nitrogen	Argon	CO2
High Pressure	0.1 CFM	25 – 100 psi	22.5 - 98 psi	29 - 119 psi	31 - 126 psi
	1.0 CFM	25 – 100 psi	24 - 98 psi	30 - 122 psi	32 - 129 psi
	50 LPM	25 – 100 psi	58 - 98 psi	31.5 - 120 psi	32.5 - 128 psi
	100 LPM	60 – 100 psi	58 - 98 psi	71 - 120 psi	75 - 128 psi
Low Pressure	1.0 CFM	5 – 25 psi	5 - 24.5 psi	7.5 - 32 psi	8.5 - 34 psi
	50 LPM	5 – 25 psi	5 - 24.5 psi	7.5 - 31.5 psi	8.5 - 33.5 psi
	100 LPM	20 – 60 psi	19.5 - 58.5 psi	24.5 - 72 psi	26.5 - 77 psi

System components included: mounting brackets and exhaust tubing to particle counter

Not included: particle counter, ISPs sample tubing, communications cables, PC, FacilityNet or Pharmaceutical Net software

HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

www.pmeasuring.com
info@pmeasuring.com



GLOBAL OFFICES

AUSTRIA
T: +43 512 390 500
E: pmsaustria@pmeasuring.com

BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 21 6113 3600
E: pmschina@pmeasuring.com

FRANCE
T: 33(0)1 60 10 32 96
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 6151 6671 632
E: pmsgermany@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmssrl@pmeasuring.com

JAPAN
T: +81 44 589 3498
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

MEXICO
T: +52 55 2271 5106
E: pmsmexico@pmeasuring.com

NORDIC
T: +45 707 028 55
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 787 718 9096
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0330
E: pmssingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300 Ext: 301
E: pmstaiwan@pmeasuring.com



Airnet®, Lasair®, and IsoAir® are registered trademarks of Particle Measuring Systems, Inc. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. ©2022 Particle Measuring Systems, Inc. All rights reserved. 09212022